


INSTRUMENT APPROACH CHART
 AERODROME ELEV. 777ft. APP.127.9 TWR.118.1
 HEIGHTS RELATED TO THR RWY 27-ELEV.750ft
 DELHI INDIA ILS RWY 27



MISSED APPROACH

Climb straight ahead. Crossing NDB(274 DP) or 5D (116.1DPN) turn RIGHT on heading 345°M to establish R-316(116.1DPN) climbing to FL65 to join holding at SAMPLA VOR(117.0 SAM) at FL65 or as instructed by ATC.

NAUTICAL MILES FROM THR RWY 27

O. C. A.		Distance (ILSDME) / Altitude information for G.P.inoperative Procedure							
CATEGORY OF AIRCRAFT	A/B	C/D	Distance(NM)	5.8D	5D	4D	3D	2D	
STRAIGHT-IN	1020	1020	Distance(NM)	5.8D	5D	4D	3D	2D	
VISUAL CIRCLING	1470	1570	Altitude(Ft.)	2600	2350	2030	1710	1390	
GP In-Operative procedure		Distance from FAF to MAPt 4.8NM							
STRAIGHT-IN	1190	1190	Ground speed (kt.)	80	100	120	140	160	180
VISUAL CIRCLING	1470	1570	Time(Min :Sec)	3:36	2:53	2:24	2:03	1:48	1:36
			Rate of descent (ft/min)	425	530	640	745	850	955

AERODROME OPERATING MINIMA	CATEGORY A		CATEGORY B		CATEGORY C		CATEGORY D	
	ALS	ALS OUT	ALS	ALS OUT	ALS	ALS OUT	ALS	ALS OUT
NORMAL MINIMA (ILS)	900	1300	900	1300	900	1300	900	1300
RESTRICTED MINIMA (ILS)	1600	2000	1600	2000	1300	1700	1300	1700
NORMAL MINIMA (GP INOP)	2000	2400	2000	2400	2400	2800	2800	3200
RESTRICTED MINIMA (GP INOP)	2400	2800	2400	2800	2800	3200	3200	3600
NORMAL CIRCLING MINIMA	3600		3600		4400		4800	
RESTRICTED CIRCLING MINIMA	3600		3600		5000		5000	

DRG. NO. AAI/ 13IALC/04/ 29.05.07

Cancellation: G-29/07